



GENERAL SPECIFICATIONS

• L.O.A	6.40 m
• Length of hull	6.25 m
• L.W.L.	6.00 m
• Width of hull	2.48 m
• Drifter draught (min)	0.70 m / 1.80 m
• Drifter ballast	300 kg
• Air draught (max)	10.40 m
• Light displacement	1 245 kg
• Engine power outboard max	8 Kw / 10 HP
• Transportable road gauge	

ARCHITECTS

- Finot Conq et Associés

EC CERTIFICATION

- Category C - 6 persons
- Category D - 6 persons

STANDARD SAIL LAYOUT AND AREA

• Mainsail	13.80 m ²
• Genoa 100 %	11.40 m ²
• Asymmetric spi	31.11 m ²
• Symmetric spi	34.77 m ²
• I	8.59 m
• J	2.40 m
• P	8.30 m
• E	2.85 m

STANDARD EQUIPMENT

CONSTRUCTION

Design made following European Directive requirements and according to EC certification.

- Monolithic hull design in polyester
- Structural counter moulding made with unidirectional fabrics laminated and stuck evenly to the hull
- Deck made of injection moulding (Fibreglass sandwich / Balsa wood / Polyester resin)
- Accessible areas covered in a «Picot» type non-slip surface
- Solid unhewn wood footrest, stuck and screwed, forms the deck hull join
- Cast iron keel, pivoted and adjusted with a manual system of lifting screw and handle. Mounted with adjustable plates
- 2 retractable polyester rudders with sleeve system
- Grey coloured hull - Anthracite grey hull decoration

DECK EQUIPMENT

RIGGING

- Standard mast 9/10 electro-polished aluminium installed on the deck, 1 level(s) of advanced cross trees
- Boom in anodised aluminium
- Standing rigging in single-strand stainless steel
- Shroud and lower shroud plates fixed to the deck hull join
- Single back-stay with cross-bracing adjusted by tackle
- 1 mainsail tackle mounted on snap shackle in cockpit bottom
- 1 Kicking strap
- 1 trimming tackle on boom
- Genoa furler
- 2 genoa sheet tracks with back and forth adjustable bearing car
- Rigging run back to cockpit
- Complete running rigging: 1 Genoa furler line, 1 Genoa halyard, 1 Main halyard, 2 reef lines
- 2 cheek blocks
- 4 clutches
- 1 Jam cleat
- 2 Belaying cleats
- 2 Bollards

WINCHES

- 2 aluminium winches (H08A): Genoa sheet, halyards and reef lines
- 1 winch handle(s)

MOORING -ANCHORING

- Self-bailing chain locker
- 1 Stainless steel bow fitting 1 stainless steel bow roller
- 4 Aluminium mooring cleats

PERSONNEL GUARDS

- 1 stainless steel 3 leg pulpit
- 2 stainless steel aft pushpits
- Stainless steel single guardrails and stanchions

COCKPIT

- Cockpit bottom self bailing
- 2 wet lockers with locks
- 2 solid wood footrests on cockpit benches
- Solid wood tiller with jointed extension

SUN DECK AND UPPER STERN

- 1 Stainless steel swimming ladder
- 1 handhold

FITTINGS

- Light oak colour Alpi woodwork
- Parquet and polyester type laminated non-slip floors
- Vinyl fabric spar ceiling on deck counter-moulding

COMPANIONWAY

- Height to deck beam: 1.45 m
- 1 sliding companionway hatch with fitted window
- Space for storing table (saloon/cockpit)

FORWARD CABIN

- Double bed (1.90 m x 1.40 m) - Foam mattress with cover
- Cubbyholes and storage space
- Cabin/saloon separation curtain
- 1 circular opening deck hatch

GALLEY

- Sink with drain
- Space for cooker
- Storage

SALOON

- Height to deck beam: 1.45 m
- 2 bench seats / Single berths (2.20 M x 0.60 M) with mattress and cover
- Storage
- 2 oilskins pegs
- 2 fixed hull portholes

ELECTRICITY

- 1 battery 12 V, 50 Amp
- 1 electrical 12 V and 6 function panel with fuses
- Navigation lights
- Lighting: Ceiling lights and lamp fittings

PLUMBING

- 1 Manual bilge pump

TRIM LEVEL

	DYNAMIC
Partition compass	■
Cockpit benches decked in natural solid wood	■
Opening cockpit locker hatch	■
Outboard engine bracket (max 30 KG)	■
1 hob stainless steel gas cooker	■
Fresh water system - 35 Litre reserve - Hand pump	■
4 removable storage nets on stainless steel rails along hull	■

OPTIONS

PACKS

PACK ELECTRONIC RAYMARINE

- Tridata Loch speedo sounder ST 60+

OTHER OPTIONS

- White coloured hull - Anthracite grey decoration
- Sail kit (4 batten mainsail with 2 reef lines - Furling genoa with UV protective strip - Lazy-jacks - Lazy-bag)
- Wind indicator Windex
- Asymmetrical spinnaker rigging with swing pole (2 sheets, 1 halyard, 1 spinnaker pole, 1 swing pole base, 1 folding pad-eye, 1 snap shackle block(s))
- Asymmetric spinnaker rigging and boom (2 sheets, 1 halyard, 1 Jam cleat, 1 aluminium swinging boom, 1 Boom lift, 1 Spinnaker boom downhaul, 2 snap shackle block(s))
- Fold-down mast kit
- Prop brackets
- Props
- Folding saloon or cockpit table
- Chemical toilet

