



Short draught keel



Shallow draught keel



Deep draught keel



GENERAL SPECIFICATIONS

• L.O.A	14.07 m
• Length of hull	13.68 m
• L.W.L.	12.01 m
• Width of hull	4.20 m
• Light displacement Deep draught keel	11 545 kg
• Air draught Standard	20.75 m
• Draft Standard Shallow draught keel Cast iron	2.40 m
• Ballast weight shallow draught	3 875 kg
• Draft Optional extra Short draught keel Cast iron	2.00 m
• Ballast weight Short draught keel	4 480 kg
• Draft Optional extra Deep draught keel Lead	2.75 m
• Ballast weight deep draught	3 850 kg
• Freshwater capacity	330 l
• Fuel oil tank capacity	200 l
• Engine power	54 HP sail drive

ARCHITECTS

• Architect Naval	P. Briand Yacht Design
• Architecture interior	Veerle Battiau

EC CERTIFICATE

- Category A - 12 persons
- Category B - 12 persons
- Category C - 12 persons

STANDARD SAIL LAYOUT AND AREA

• Mainsail	55.50 m ²
• Genoa max	60.40 m ²
• Spinnaker	140.00 m ²
• I	17.35 m
• J	5.33 m
• P	17.00 m
• E	5.50 m

SAIL LAYOUT AND AREA REGATA ALUMINIUM

• Mainsail	60.70 m ²
• Genoa max	52.50 m ²
• Spinnaker	151.00 m ²
• I	18.35 m
• J	5.51 m
• P	18.00 m
• E	5.50 m

STANDARD EQUIPMENT

CONSTRUCTION

Design made following European Directive requirements and according to EC certification.

- Monolithic hull design in polyester
- Monolithic structural counter moulding laminated and stuck to hull
- Injection moulded deck (Sandwich / Glass fibre / Balsa wood / Synthetic resin)
- All deck and work access area surfaces are non-slip
- Monolithic deck counter moulding cemented to deck
- Deck hull join screwed, stuck and banded with 1 solid wood bulwark, screwed
- Stern deck laminated
- Keel Short draught keel (optional extra) - bulbous - Cast iron
- Keel Shallow draught keel (Standard) - torpedo type bulb shape - Cast iron / Cast iron keel body and bulb
- Keel Deep draught keel (optional extra) - straight - Lead
- The keel is fixed to the boat by a system of screws and stainless steel veneer
- Underhung balanced rudder in fibreglass sandwich and polyurethane foam - Injection moulded stock - Self-aligning rocker bearings with race bearings and rollers
- White coloured hull - Grey hull decoration

DECK EQUIPMENT

RIGGING

- Standard 9/10 electro-polished aluminium mast, 3 level(s) of cross trees advanced, fitted to keel
- Socket fitting - 2 Collar tie rods - 10 Blocks
- 3 Retractable steps
- Boom in anodised aluminium
- Kicking strap Rigid mechanical
- Standing rigging DYFORM fractional discontinuous
- Single backstay - Hydraulic piston adjusted
- Standard fore stay ROD - Plate fixed in chain locker
- Genoa furler - Drum on deck
- 1 Mainsail sheet track at bottom of cockpit
- 2 Genoa sheet tracks - Ball bearing genoa car adjustable under tension - 2 Track end fittings with lead blocks for back and forth control - 2 Genoa sheet return blocks - 2 Clutches on deck for the back and forth with plates and blocks - 3 Furling line blocks - Lead - Jammer
- Complete running rigging Dyneema®: 1 Genoa halyard - 1 Genoa furler line - 2 Genoa sheets - 2 Back and forth Genoa traveller - 1 Main halyard - 1 Mainsail foot - 1 Mainsail sheet in cockpit - 3 reef lines
- 12 sheet clutches
- 2 5 sheave cheek blocks at mast level
- 2 Deck organiser on the deck house
- Spinnaker pre-rigging and fittings: 2 Spinnaker sheet plates - 2 Spinnaker arm plates - 2 Spinnaker pole down haul plates

WINCHES

Aluminium Harken winches self tailing:

- 1 Mainsail/spinnaker winch 44.2 STA on cockpit coaming
- 2 Rigging winches 44.2 STA on deck house
- 2 Genoa sheet winches 53.2 STA on cockpit coamings
- 2 winch handle(s)

BOW - MOORING - ANCHORING

- 1 Stainless steel bow fitting - Asymmetric spinnaker securing point
- 1 Stem roller in stainless steel removable
- Self-bailer chain locker with clench eye
- Vertical electric windlass 1000 W - Breaker - Relay box 12 V - Remote control with wire
- Sail locker
- 6 Aluminium mooring cleats - Stainless steel guards bolted to deck hull join

PERSONNEL GUARDS

- 1 Stainless steel pulpit
- 2 stainless steel aft pushpits - 1 Central pulpit - linked by 2 opening guardrails with snap shackles
- Guardrails with double adjusting turnbuckles, Stainless steel stanchions and bases
- Side opening in port and starboard guardrails
- Flag pole mountings - Ring lifebuoy bracket
- 2 Compound handrails fitted to deck by side porthole covers
- 2 Jointed plates for harness (at companionway)

COCKPIT

- Cockpit bottom self bailing
- 1 Locker under each cockpit bench
- 1 Compartment, aft of steering station To port
- 1 Gas cylinder locker, aft of steering station
- 1 Life raft locker in cockpit bottom - Gas piston lid
- Cockpit bench seats - Plain solid wood decked helmsman seating
- 2 Steering wheel consoles in lacquered aluminium: 2 Black lacquered aluminium steering wheels, covered (900 mm diameter) - 2 Steering Gear - Chain and metal cable transmission linked to sector
- 1 Emergency tiller
- 2 Steering compass
- Engine control and dashboard at end of starboard cockpit bench
- Spaces for navigation electronics (optional extra) recessed into port and starboard cockpit benches
- 2 part entrance door in PMMA - 1 Sliding hatch made of PMMA

STERN DECK

- Stern deck Open
- 1 Stainless steel swimming ladder
- 1 Shower cold water

FITTINGS

- Light oak colour Alpi woodwork
- Parquet type laminated floors

COMPANIONWAY

- Height to deck beam: 1.95 m
- Moulded wood steps with non-slip surface
- 2 Stainless steel guardrails

FORWARD CABIN

- Height to deck beam: 1.93 m
- Central double bed Island berth (2.00 m x 1.50 m) - Marine mattress - Padded bedstead
- Hanging locker - 2 Drawers - Storage cupboard - 1 Dressing table - Cubbyholes along the hull
- 1 Deck hatch with mosquito blind (1 Step under spar ceiling for emergency exit)
- 2 Fixed hull porthole(s)

FORE WASHROOM

- Height to deck beam: 1.93 m
- Washroom moulded in one piece to be watertight
- Separate shower bowl Polyester - Shower - Mixer tap - Shower guard PMMA
- Manual marine toilet - Seat
- 1 Rigid sewage tank (80 litres)
- Worktop with square synthetic resin washbasin - Mixer tap - Beading Stainless steel
- Storage cupboard with drawers and Door - 1 Cubby hole locker
- Toilet accessories: Paper dispenser - Rubbish bin
- 2 Mirrors
- 1 Opening deck hatch with shutter

SALOON

- Height to deck beam: 1.94 m
- L-shaped bench seat - double density foam
- 1 Rectangular saloon table - Solid wood frame - Handhold - 2 Stainless steel legs
- 2 Removable seats - Stainless steel legs - matching saloon
- Starboard sofa bench
- Closed cubbyholes - Storage under bench seats
- Leather covered stainless steel handrails under coamings
- 2 Opening deck hatch(es) with blind / mosquito nets
- 2 Fixed hull porthole(s)
- 1 Permanent ventilation system

GALLEY TO STARBOARD

- Height to deck beam: 1.97 m
- T-shaped kitchen
- Worktop in varnished wood and synthetic resin - Solid wood beading - Handrails
- Rectangular sink - 1 Stainless steel basin - Mixer tap - 1 Closed drain rack
- 1 2 hob gas cooker on mounting - Seat / Wooden worktop
- 1 Front opening evaporator fridge - 12 V - 100 litres - Storage baskets
- 1 Cool box top opening - 60 litres
- Kitchen accessories: Cutting board - Rubbish bin - Sponge holder
- Closed cubbyholes - Storage - Storage cupboard with drawers - Cutlery drawer
- Leather covered stainless steel handrail under coaming
- 4 opening portholes with blinds on coaming

CHART TABLE TO PORT

- Height to deck beam: 1.95 m
- L-shaped chart table desk - Space for charts and navigation instruments along the hull - Space for office facing companionway
- 1 Adjustable swivel seat in PVC - Stainless steel legs
- Electrical panel - Access to charger and to electrical connexion
- Navigation instrument panels fitted in closed cubbyholes
- Closed cubbyholes - glove boxes - Storage
- Handhold - Leather covered stainless steel handrail under coaming
- 1 Leather covered stainless steel hand rail on partition Aft washroom
- 2 opening portholes with blinds on coaming
- 1 White/red light fitting

PORT AFT WASHROOM

- Height to deck beam: 1.95 m
- Shower tray grating - Shower - Mixer tap
- Manual marine toilet - Seat
- Worktop with square synthetic resin washbasin, Mixer tap - Stainless steel beading
- Storage cupboard with drawers 'a l'anglaise' and Door
- Toilet accessories: Paper dispenser - Rubbish bin
- 2 Mirrors
- 2 opening portholes with blinds on coaming

AFT CABIN

- Height to deck beam: 1.94 m
- More space in port cabin than in starboard
- 2 Cabins each with
 - 1 Double bed (To port 2.00 m x 1.40 m / 1.20 m - To starboard 2.00 m x 1.30 m / 1.10 m) - Marine mattress
 - PVC hanger closets on stainless steel rails - 1 Drawer - Storage - glove boxes
 - 1 Opening portholes with blinds on coaming
 - 1 Porthole opening on cockpit with blind
 - 1 Fixed hull porthole

ENGINE

- Engine YANMAR Diesel 54 hp
- Reverser Sail Drive
- Engine control - Key ignition - Control panel in cockpit To starboard
- Engine compartment: Soundproofing foam - Ventilation: 2 Air intakes and 1 powered air expulsion
- 1 ALTERNATOR 12 V / 80 Amperes
- 1 Rotomoulded diesel oil tank, 200 l (under starboard aft berth) - 1 Electrical gauge - Stop valve - 1 Lockable deck filler (starboard aft cockpit)
- Filters :Sea water - Diesel - Decanter
- Foldaway three-blade propeller
- 1 Engine access through companionway - 2 Engine access through aft cabins

ELECTRICITY

- 12 V circuit - 220 V circuit
- 2 service batteries 110 Amperes - 1 Battery for engine 110 Amperes - Battery switch
- 1 Charger 40 Amperes - 1 Shore power socket 220 V - Charge divider
- Electrical panel backlit (12 V / 220 V) (Circuit breakers - Voltmeter 12 V / 220 V - Ammeter - Water gauge - Fuel gauge - Battery warning - Fuel warning - Water warning)
- 1 Socket 12 V - 7 Sockets 220 V
- Interior lighting: Overhead lights LED
- Navigation lights LED: Navigation and mooring lights on mast - Port/ starboard prow light on pulpit - Sternlight on pushpit
- Wire runs for options cables

PLUMBING

- 2 rotation moulded freshwater tanks (330 l Under forward berth - 200 l under port aft berth) - 2 Deck fillers - Tank selection with ¼ by-pass valves
- Pressurised electric water pump - Expansion chamber - System protection filter
- Electric water heater 40 L (Operation off engine or on 220 V electrical system)
- 1 Rigid sewage tank (80 litres)
- Electrical shower drain pumps
- 1 Electric bilge pump - 1 Manual bilge pump

GAS

- Box for 1 gas bottle in cockpit
- Supply system in copper - Regulator valve - Safety tap

TRIM LEVEL

	DYNAMIC	AMBITION
Removable aft beam	■	■
Cockpit bottom decked in natural solid wood	■	■
2 Waterproof cockpit speakers	■	■
Hot water cockpit shower hose cold water	■	■
Flexible reading lights LED in saloon and forward cabin	■	■
Leather covering on stainless steel guardrails in saloon	■	■
grating / table mat on saloon table	■	■
Leather seat and chart table blotter Moka	■	■
Electric toilet Quiet Flush in forward washroom	■	■
Rigid reserve WC rotation-moulded (80 l) in aft washroom	■	■
2 Additional service batteries 110 amperes	■	■
Shore freshwater supply		■
TV LCD 20" - Player DVD / CD / MP3 in the saloon		■
Cooker Oven Grill in stainless steel 3 de luxe hobs		■
12V refrigeration unit in icebox with top opening		■
Microwave oven 220V		■

OPTIONS

PACKS

PACK ELECTRONIC RAYMARINE

Cockpit:

- 2 Notches colors TFT ST70 (Loch - Speedometer - Depth sounder - Weather vane - Anmomtre)
- Multifunction screen E80 colour 8.4" (GPS, tracker, Cartography chart mapper Navionics Gold, supplied without chart)
- Pilot SPX ST70 - LS 50 - Integrated gyrocompass - Control console

Mast foot:

- 3 Notches colors 6.5" ST70+ - Controls in the cockpit

PACK REGATA

- Mast aluminium 3 levels - Rigging ROD discontinuous - Backstay PBO - Forestay Tuff Luff
- 2 Rigging winches Harken H48.2 STA
- 2 Genoa sheet winches H60.2 STA
- 2 Winches Main sheet / Spinnaker Harken H48.2 STA
- Symmetrical spinnaker rigging / asymmetric
- Carbon spinnaker pole Black

PACK EASY DOCKING

- Bow thruster retractable
- Mooring kit (Anchor FOB 20 kg, 32 M of 10 mm chain, 48 M 18 mm rope) - 4 Mooring ropes - 6 Fenders

OTHER OPTIONS

- Control Smartcontroller RAYMARINE
- Receiver AIS RAYMARINE
- VHF RAYMARINE 240E
- Radar (radome only) RAYMARINE
- Offset control keyboard for E series screen
- PC interface
- Grey coloured hull - Anthracite grey hull decoration
- 1 Electrical rigging winch Harken 44.2 STAEH (In replacement of standard)
- Black carbon mast for regatta pack (Carbon mast 2 levels - Boom aluminium - Rigging ROD - Backstay PBO - Forestay tuff luff)
- Track Facslide - Bearing sliders
- Fore stay sail bolt plate
- Natural solid wood lathed deck
- Grey deck house hood
- Grey cockpit cushions
- Double berth in saloon
- Anti-roll sheets
- Porthole mosquito nets
- Crockery kit marked
- TV aerial
- Heating
- Air conditioning
- Inverter 12 V / 220 V - 2000 VA
- Electric toilet Aft